



**Part Number: 1800F**

Audio Cable, 1 Pair 24 AWG BC, Shielded, Riser

**Product Description**

Digital Audio Cable, 1 Pair 24 AWG stranded (42x40) bare copper pair with Datalene® insulation, fillers, + 95% tinned copper braid, drain, Riser, flexible PVC jacket.

**Technical Specifications**

**Product Overview**

Environmental Space:	Indoor - Riser
----------------------	----------------

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
24	42x40	BC - Bare Copper	0.024 in	1

Conductor Count:	2
Conductor Size:	24 AWG

**Insulation**

Material	Material Trade Name	Nominal Diameter
FHDPE - Foamed High Density Polyethylene	Datalene®	0.058 in

**Color Chart**

Number	Color
1	Red & Black

**Outer Shield Material**

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
French Braid	TC - Tinned Copper	95 %	BC - Bare Copper	26	Stranded mm

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.211 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR
23.7 Ohm/1000ft	6.42 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12 pF/ft	26 pF/ft

**Inductance**

Nominal Inductance
0.18 µH/ft

## Impedance

### Nominal Characteristic Impedance

110 Ohm

## High Frequency (Nominal/Typical)

### Nom. Insertion Loss

0.46 dB/100ft

0.67 dB/100ft

0.7 dB/100ft

0.83 dB/100ft

1.04 dB/100ft

1.09 dB/100ft

1.3 dB/100ft

1.66 dB/100ft

1.75 dB/100ft

2.23 dB/100ft

2.89 dB/100ft

3.07 dB/100ft

3.71 dB/100ft

4.53 dB/100ft

4.78 dB/100ft

7.11 dB/100ft

## Delay

### Nominal Velocity of Propagation (VP) [%]

76 %

## High Freq

### Frequency [MHz]

0.384 MHz

0.706 MHz

0.768 MHz

1.024 MHz

1.411 MHz

1.536 MHz

2.048 MHz

2.822 MHz

3.072 MHz

4.096 MHz

5.645 MHz

6.144 MHz

8.192 MHz

11.29 MHz

12.288 MHz

24.576 MHz

## Current

### Max. Recommended Current [A]

2.75 Amps per conductor @ 25°C

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

Non-UL Temp Rating: 60°C

Operating Temp Range: -20°C To +60°C

## Mechanical Characteristics

UV Resistance: Yes - Black only

Bulk Cable Weight: 24 lbs/1000ft

Max Recommended Pulling Tension:	41.5 lbs
Min Bend Radius/Minor Axis:	2.25 in

## Standards

NEC/(UL) Specification:	CL2R
Other Specification:	AES/EBU Digital Audio

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1666 Riser
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Footnote
1800F B591000	Black, Matte	C
1800F B59500	Black, Matte	C
1800F B59U1000	Black, Matte	
1800F B5910000	Black, Matte	
1800F B5910000	Black, Matte	
1800F G7XU1000	Blue, Matte	
1800F U90U1000	Gray, Matte	
1800F G7WU1000	Green, Matte	
1800F G7VU1000	Red, Matte	
1800F Z4BU1000	Violet Z4B	
1800F G8MU1000	Yellow, Matte	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.